

ETL Intertek Testing listed to UL924 Standard for Emergency Lighting

**Photoluminescent Acrylic EXIT Sign
50-foot viewing distance**

Item-No:	Description:	Dimensions:
	<p>50 foot viewing distance energy-efficient Photoluminescent Acrylic EXIT Sign:</p> <p>Red Acrylic Panel with photoluminescent yellowish sub-surface printed letters</p> <p>600031 EXIT (no chevrons)</p> <p>600032 <EXIT (The Chevron is sub-surface printed.)</p> <p>600033 EXIT> (The Chevron is sub-surface printed.)</p> <p>600034 <EXIT> (The Chevrons are sub-surface printed.)</p> <p>Green Acrylic Panel with photoluminescent yellowish sub-surface printed letters</p> <p>600035 EXIT (no chevrons)</p> <p>600036 <EXIT (The Chevron is sub-surface printed.)</p> <p>600037 EXIT> (The Chevron is sub-surface printed.)</p> <p>600038 <EXIT> (The Chevrons are sub-surface printed.)</p> <p>Black Acrylic Panel with photoluminescent yellowish sub-surface printed letters</p> <p>600039 EXIT (no chevrons)</p> <p>600040 <EXIT (The Chevron is sub-surface printed.)</p> <p>600041 EXIT> (The Chevron is sub-surface printed.)</p> <p>600042 <EXIT> (The Chevrons are sub-surface printed.)</p> <p>Also available DOUBLE-sided: Add -DB to Item-Number A double-sided Sign requires a Wire Suspension Set – see Page 2.</p>	<p>8-3/4 inch tall</p> <p>17-1/4 inch wide</p> <p>Each sign has four holes. Hole diameter: 3/8 inch</p>



Compliances

Photoluminescent Exit Sign

- ✓ In compliance with IBC and IFC codes
- ✓ In compliance with NFPA 101-*Life Safety Code*
Before installation it must be determined that there is a minimum of 5 fc (54 lux) of fluorescent illumination on the face of the sign at all times of building occupancy.
- ✓ OSHA compliant
- ✓ Listed to Standard UL924 by ETL Intertek Testing
- ✓ Four Holes for flat wall mount.
- OPTIONALLY available:
One Set of 4 Stand-Off Barrels (Item-No.: 600058).
Wire Suspension Set to hang sign up to 24 inches away from the ceiling (Item-No.: 600059).
- ✓ Listed for high-location and floor-proximity installation = impact resistance tested by ETL!

ETL Intertek Testing listed to UL924 Standard for Emergency Lighting

**Photoluminescent Acrylic EXIT Sign
50-foot viewing distance**

Item-No:	Acrylic Sign Accessories Description:	Dimensions:
600058	<p>Accessories for Photoluminescent Acrylic EXIT Sign:</p> <p>Set of 4 Stand-Off Barrels for protruding wall installation</p> 	1-inch barrels
600059	<p>Wire Suspension Set to hang sign up to 24 inches from the ceiling</p> 	2 cables at 24 inch length with 2 ceiling-mount barrels

Acrylic Exit Sign Benefits

- No energy consumption: no electricity cost; green design
- No maintenance: no bulbs, no battery replacement
- Non-toxic, non-radioactive
- No disposal cost
- Easily movable should egress routing change
- Elegant sub-surface printed design
- Consistent, uniform EXIT legend illumination
- Visible at 50 feet
- Recyclable Acrylic
- LEED points qualified